

N212 SAND REC



0919 nero



0614 amaranta



0210 white - 0120 white PFP



5316 new blu cina



N212 SAND REC

Applications

> Swimwear > Beachwear

An excellent choice for your fashion beachwear collections. Made with 100% recycled polyamide, it is a very versatile fabric, remarkable for its convenience, flexibility and simplicity. Ideal for a first approach to sustainable materials.



Composition			
Recycled Polyamide	Elastane		
80%	20%		
Weight (±5%)	Width (+3%/-2%)		
175 g/m²	263 g/m lin.	150 cm	
Courses	Wales	Tolerance for composition (standard ASTM)	
45/cm	22/cm	±3%	
Dimensional Change of fabric after HL AATCC 135-2015 (1 wash, normal cycle at 41 degree Celsius line dry)	Max	Max	
	-5%	-5%	
	Width	Length	
Resistance to pilling ASTM D 3512-Random tumble at 30 minutes photographic rating STD	4 to 4.5		
Ultraviolet Protection Factor (U.P.F.) AATCC 183-2010	50+		
Stretch to dynamometer (±15%) ASTM D 4964 - LOAD 20 LBS	115%	185%	
	Width	Length	
	(min 98% - max 132%)	(min 157% - max 213%)	
Modulus % elongation (30% - 50% - 70%)	30%	50%	70%
	0.25 - 0.6	0.7 - 1.4	1.4 - 2.9
	Width Lbs	Length Lbs	
Care labelling codes			

AATCC Standards

COLOUR	CHLORINATED WATER	LIGHT	WATER 38°C							SEA WATER 38°C							PERSPIRATION							CROCKING		WASHING 49°C						
	AATCC 162	AATCC 16-20 AFU	AATCC 107							AATCC 106							AATCC 15							AATCC 8		AATCC 61-2A						
	C.C.	C.C.	C.C.	AC	CO	PA	PL	PC	WO	C.C.	AC	CO	PA	PL	PC	WO	C.C.	AC	CO	PA	PL	PC	WO	S.CO	S.CO	C.C.	AC	CO	PA	PL	PC	WO
0210	3	3	4.5	5	5	5	5	5	5	4.5	5	5	5	5	5	5	4.5	5	5	5	5	5	5	5	5	4.5	5	5	5	5	5	
0120	3	3	4.5	5	5	5	5	5	5	4.5	5	5	5	5	5	5	4.5	5	5	5	5	5	5	5	5	4.5	5	5	5	5	5	
0614	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4	3	4	4.5	4.5	3.5	4.5	4.5	4.5
5316	3.5	3.5	4.5	4.5	4.5	3.5	4.5	4.5	4	4.5	4.5	4.5	3.5	4.5	4.5	3.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	3	4	4.5	3.5	3.5	4.5	4.5	4
0919	4.5	4.5	4.5	4.5	4	4	4.5	4.5	4	4.5	4.5	4	4	4.5	4.5	4	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	3	4.5	4.5	4	4	4.5	4.5	4

ISO Standards

COLOUR	CHLORINATED WATER	LIGHT	WATER			SEA WATER			ALKALINE PERSPIRATION PH 8.0			ACID PERSPIRATION PH 5.5			CROCKING		WASHING 40°C		
	ISO 105-E03	ISO 105-B02	ISO 105-E01			ISO 105-E02			ISO 105-E04			ISO 105-E04			ISO 105-X12		ISO 105-C06 A2S		
	C.C.	C.C.	C.C.	CO	PA	C.C.	CO	PA	C.C.	CO	PA	C.C.	CO	PA	S.CO	S.CO	C.C.	CO	PA
0210	2-3	3	4-5	5	5	4-5	5	5	4-5	5	5	4-5	5	5	5	5	4-5	5	5
0120	2-3	3	4-5	5	5	4-5	5	5	4-5	5	5	4-5	5	5	5	5	4-5	5	5
0614	3-4	4-5	4-5	4-5	4-5	4-5	4-5	4-5	4-5	4-5	4-5	4-5	4-5	4-5	4	3	4-5	4-5	4
5316	2-3	3-4	4-5	4-5	4	4-5	4-5	4	4-5	4-5	4	4-5	4-5	4	4-5	3	4-5	4	4
0919	4-5	4-5	4-5	4-5	4	4-5	4-5	4	4-5	4-5	4	4-5	4-5	4	4-5	3	4-5	4-5	4


N212 SAND REC



recycled



high chlorine resistance



two way stretch



perfect fit



UV protection



Available colors: the 4 colors presented in this page are always available for sampling. If you would like to choose a color from the main Polyamide color card, you can enjoy a MCQ of only 70 mts for bulk orders. However, the resulting color shade and the color fastness performance may be slightly different. We will submit to your attention a lab dip swatch for approval before going on with the bulk production.

Special notes/warnings: we recommend carrying out lab tests for color matches, molding, bonding and applications on fabrics in order to prevent problems from arising during garments production. Please carefully check physical data and color fastness forecasts.